



T-220-SS

T-220-SS

PERFORMANCE¹

- Capacity: Up to 2000 tons/hour
- Projection: Up to 46 m (150 ft)

DIMENSIONS

- Overall width: 2794 mm (110 in.)
- Overall height: 3556 mm (140 in.)
- Working height: 1524 mm (60 in.)
- Weight: 2177 kg (4800 lb)

CARRIER

- Power: Tractor of 150 kW (200 hp)
to 224 kW (300 hp) at 2200 rpm

POWER TRANSMISSION

- Drive from PTO through belt and pulley at rear
and gear box at front
- Drive shaft protected in central push frame

AUGERS

- Quantity: Two (2)
- Diameter: 508 mm (20 in.)
- Type: One piece ice type design,
bolted and interchangeable

IMPELLER

- Diameter: 990 mm (39 in.)
- Blades: Five (5) blades, bolted
- Rotation: 150° total, flat discharge
to the right

LOADING CHUTE

- Diameter: 380 mm (15 in.)
- Rotation: 270°

OPTIONAL EQUIPMENT

- Hydraulic steering vanes
- Hydraulically extendable loading chute

¹ Depending on snow conditions



ISO 9001:2000

Specifications on this brochure may be changed without prior notice.
Revised : April 2007

QUEBEC CITY
184 Route 138
Cap-Santé, Quebec GOA 1L0
Telephone: 418.285.1811
Toll free: 1.800.463.3882
www.rpmttechgroup.com

LAVAL
2220 Michelin Street
Laval, Quebec H7L 5C3
Telephone: 450.687.3280
Toll free: 1.800.631.9297
info@rpmttechgroup.com